


THREADS	CODE	X	SW
1/4-18 NPT MALE; DIN EN 837	02	30 [1,18]	19 [0,75]
1/2-14 NPT MALE; DIN EN 837	04	37 [1,46]	22 [0,87]
G 1/4 B MALE; DIN EN 837	13	25 [0,98]	19 [0,75]
G 1/2 B MALE; DIN EN 837	15	37 [1,46]	22 [0,87]
M20x1,5 MALE; DIN 3852 TEIL 1	16	37 [1,46]	22 [0,87]
1/4-18 NPT FEMALE	25	20 [0,79]	19 [0,75]
1/2-14 NPT FEMALE	50	26 [1,02]	27 [1,06]
G1/2 FEMALE; DIN EN 837	51	26 [1,02]	27 [1,06]

This drawing includes confidential information which is the property of ASHCROFT INC. This copy is loaned for a specific purpose, with the understanding that it will not be reproduced or used for any other purpose or disclosed to others, and it will be returned on demand.

Dimensions in mm [inch]



General Dimension  
F5509, NG100, 0,4 ÷ 25 bar

Rev.	Description	Date	Na.
B	Design change	19.06.18	Krott
A	Drawing updated	07.02.17	Krott



DWG. NO.  
B 076 I 1-F5509-NG100-0,4-25 bar

All specifications are subject to change without notice.