





THREADS	CODE
1/4-18 NPT MALE; DIN EN 837	02
3/8-18 NPT MALE	03
1/2-14 NPT MALE; DIN EN 837	04
9/16-18 UNF-2B FEMALE; AMINCO; HP	09
G 1/4 B MALE; DIN EN 837	13
G 3/8 B MALE; DIN EN 837	14
G 1/2 B MALE; DIN EN 837	15
M20x1,5 MALE	16
1/4-18 NPT FEMALE	25
M16x1,5 FEMALE; HP	78
7/16-20 UNF-3A 37° FLARE	EJ
PF 1/4 B MALE; (JIS B 07505/0202)	KJ
PF 1/2 B MALE; (JIS B 07505/0202)	KN
PF 3/8 B MALE; (JIS B 07505/0202)	KP
R 1/2 MALE; ISO 7-1	KQ
R 3/8 MALE; ISO 7-1	KR
9/16-18 UNF for 3/8 O.D. TUBING	RF
SAE 7/16-20 UNF STRAIGHT THREAD	RW

This drawing includes confidential information which is the property of ASHCROFT INC. This copy is loaned for a specific purpose, with the understanding that it will not be reproduced or used for any other purpose or disclosed to others, and it will be returned on demand.

		Date	Name
Drawn		20.01.09	J. Krott
Checked		22.03.17	Th. Wel

Rev.	Description	Date	Na.
B	∅6 was ∅5,5	21.03.17	Krott
A	Updated drawing	10.10.11	Krott

Dimensions in mm [inch]

General Dimension

T5500, NG160, Lower, UF

DWG. NO.

B 076 I 1-T5500-NG160-L-UF

All specifications are subject to change without notice.