

# All stainless steel pressure gauge

## Model 5008

According EN 837-1  
Nominal size 63 mm  
Accuracy Class 1,6



### Features

- Rugged stainless steel construction
- Socket and case welded
- Protection IP66 & IP67
- Overload protection 130 %
- Dry or liquid filled

### Ranges

-1 ... 0 bar up to 0 ... 1000 bar  
-30 in. Hg ... 0 psi up to 0 ... 15.000 psi

### Applications

Chemical and petrochemical industry  
Machine and apparatus construction  
Food and beverage industry  
Pulp and paper industry



Technical specification	5008
Dial size in mm	63
Construction	Open front cylindrical case with fill plug and vent valve on top
Ring design	Crimped ring
Measuring principle	Bourdon tube
Range in bar	1 1,6 2,5 4 6 10 16 25 40 60 100 160 250 400 600 1000 -1/0 -1/0,6 -1/1,5 -1/3 -1/5 -1/9
Range in psi	15 30 60 100 150 200 300 400 600 1000 1500 2000 3000 5000 6000 10.000 15.000
Range in in.Hg/psi	-30/0 -30/15 -30/30 -30/60 -30/100 -30/150 -30/300
Overpressure limit	130 % F.S., short time
Pressure type	Gauge, vacuum and compound
Process connection	G ¼ B male according EN 837, R ¼ male tapered according JIS or BSP ½ or ¼ NPT male according ANSI/ASME B1.20.1
Connection location	Lower, center back
Material	
Pressure connection	Stainless steel 316L (1.4404)
Tube	Stainless steel 316L (1.4404)
Case/bayonet ring	Stainless steel 304 (1.4301), optional 316L (1.4404)
Window	Instrument glass, optional laminated safety glass or acrylic glass
Dial	Aluminum, black markings on white background
Pointer	Plastic, black
Movement	Stainless steel 304 (1.4301)
Accuracy	Class 1,6 (1,6 % F.S.)
Permissible	
Ambient temperature	-25 ... 60 °C
Medium temperature	Max. 200 °C (dry), max. 100 °C (liquid filled)
Storage temperature	-40 ... 60 °C
Temperature effect	Max. 0,3 % / 10 K
Conformity according to RL 2014/34/EU appendix X for mechanical equipment in potential hazardous areas	Optional, Marking CE Ex II 2 GD c IIC Tx, T <sub>amb</sub> -20 ... 60 °C File no. 35118307 at notified body 0044, TUV NORD CERT Used harmonized standards: DIN EN ISO 80079-36:2016-12 and DIN EN ISO 80079-37:2016-12 (only with safety glass)
Protection according EN 60 529/IEC 529	IP66 & IP67
Filling liquid	Glycerin or silicone
Mounting	Standard stem, optional flush, U-clamp or surface
Weight dry/filled in kg	0,2/0,3
Accessories, options	Diaphragm seals, valves

